



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING-DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/623,586	07/22/2003	Yoon-Seop Eom	1349.1238	5856
21171 7590 05/11/2007 STAAS & HALSEY LLP SUITE 700 1201 NEW YORK AVENUE, N.W. WASHINGTON, DC 20005			EXAMINER WILLS, LAWRENCE E	
			ART UNIT 2609	PAPER NUMBER
			MAIL DATE 05/11/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

10/623,586

Applicant(s)

EOM ET AL.

Examiner

Lawrence E. Wills

Art Unit

2609

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 22 July 2003.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-20 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-20 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
- 1) ☒ Certified copies of the priority documents have been received.
 - 2) ☐ Certified copies of the priority documents have been received in Application No. _____.
 - 3) ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892) ✓
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date 10/03/2005;06/27/2005. ✓
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____.
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: _____.

DETAILED ACTION

Information Disclosure Statement

1. The information disclosure statement (IDS) submitted on October 3, 2005 was filed after the mailing date of the application on July 22, 2003. The submission is in compliance with the provisions of 37 CFR 1.97. Accordingly, the information disclosure statement is being considered by the examiner.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

3. Claims 1-3, 5-7, 9-12,14, and 16-18 are rejected under 35 U.S.C. 102(b) as being anticipated by Akiyama (U.S. Patent No. 5,872,635).

With regard to claim 1, Akiyama teaches an image forming apparatus, comprising an engine mechanism 25 (Figure 1,2A, 2B) to perform a printing operation with respect to print data, a video unit 26 to convert the print data into image data readable by the engine mechanism 25 (Column 3, lines 28-32, an image forming apparatus according to the present invention comprises image forming means for forming an image on a recording medium on the basis of pixel data generated by image processing means for generating pixel data), and an engine

Art Unit: 2609

control unit 25a to control the engine mechanism 25 to perform the printing operation with the image data. The video unit 26 comprises a processor 16 that controls the video unit 26 and the engine control unit 25a. (Figure 2B shows an engine control unit that controls engine mechanism; Figure 1 shows a single processor driving video and engine units.)

With regard to claim 2, Akiyama teaches an image forming apparatus further comprising a system bus 24 to directly connect the engine control unit 25a with the processor 16, wherein the engine control unit 25a drives the engine mechanism 25 in accordance with control by the processor. (Figure 1, in addition, column 5, lines 51-54, When video data for one page are stored in the frame memory 23, the CPU 16 outputs a print command to an engine unit 25 via a video interface 24, and outputs the video data stored in the frame memory 23 to the engine unit 25)

With regard to claim 3, Akiyama teaches an image forming apparatus comprising a bi-directional data bus and a control bus. (Figure 1 shows Video I/F, a bi-directional bus, in addition, Figure 2B shows each signal of the bi-directional bus, and Figure 3 lists each signal)

With regard to claim 5, Akiyama teaches an image forming apparatus, wherein the processor reads the state information stored in the memory to check a state of the engine mechanism, and transmits the image data to the engine control unit to perform the printing operation. (Column 2, lines 30-37, When 1-byte command information is supplied from the video controller to the engine controller in synchronism with the signal /SCLK, the engine

Art Unit: 2609

controller sends back 1-byte status information to the video controller. This command information includes two commands, i.e., a status request command for checking the status of the printer engine, and an execution command for instructing the printer to perform some operation.)

With regard to claim 6, Akiyama teaches an image forming apparatus, comprising: an engine mechanism to perform a printing operation with respect to print data; a video unit to convert the print data into image data readable by the engine mechanism; an engine control unit to control the engine mechanism to perform the printing operation with respect to the image data in accordance with control by the video unit; a bi-directional parallel bus to directly connect the video unit and the engine control unit; and a single processor to drive the video unit and the engine control unit. (Column 3, lines 28-32, an image forming apparatus according to the present invention comprises image forming means for forming an image on a recording medium on the basis of pixel data generated by image processing means for generating pixel data. In addition, Figure 2B shows an engine control unit that controls engine mechanism; Figure 1 shows a single processor driving video and engine units with a bi-directional bus.)

With regard to claim 7, Akiyama teaches an image forming apparatus, wherein the video unit 26 comprises the processor 16. (Figure 1, in addition, column 5, lines 35-39 a controller unit (or printer controller) 26 includes components designated by reference numerals 16 to 24 (to be described below). A CPU 16 receives coded image information (code data)

Art Unit: 2609

from an external apparatus 27 such as a host computer via an external interface 17 upon execution of a control program stored in a ROM 19.)

With regard to claim 9, Akiyama teaches an image forming apparatus, wherein the processor 16 reads the state information stored in the memory to check a state of the engine mechanism, and transmits the image data to the engine control unit to perform the printing operation. (Column 2, lines 30-37, When 1-byte command information is supplied from the video controller to the engine controller in synchronism with the signal /SCLK, the engine controller sends back 1-byte status information to the video controller. This command information includes two commands, i.e., a status request command for checking the status of the printer engine, and an execution command for instructing the printer to perform some operation.)

With regard to claim 10, Akiyama teaches an image forming apparatus, comprising: an engine to perform a printing operation according to image data, a controller to control the engine to perform the printing operation, and a converter to convert received print data into the image data, the converter comprising a single processor to drive the converter and the controller. (Column 3, lines 28-32, an image forming apparatus according to the present invention comprises image forming means for forming an image on a recording medium on the basis of pixel data generated by image processing means for generating pixel data. In addition, Figure 2B shows an engine control unit that controls engine mechanism; Figure 1 shows a single processor driving video and engine units with a bi-directional bus.)

With regard to claim 11, Akiyama teaches an image forming apparatus, wherein the processor 16 is a microprocessor CPU. (Figure 1 describes the processor 16 as a CPU)

With regard to claim 12, Akiyama teaches an image forming apparatus, wherein the controller is an application specific integrated circuit (ASIC). (Column 12, lines 66-67 thru column 13, line 1 Note that the present invention may be applied to either a system constituted by a plurality of devices or an apparatus consisting of a single device.)

With regard to claim 14, Akiyama teaches an image forming apparatus, further comprising a bus to directly connect the controller with the processor. (Figure 1 shows a single processor driving video and engine units with a bi-directional bus.)

With regard to claim 16, Akiyama teaches an image forming apparatus wherein the controller is integrated into a single chip together with the processor. (Column 12, lines 66-67 thru column 13, line 1 Note that the present invention may be applied to either a system constituted by a plurality of devices or an apparatus consisting of a single device.)

With regard to claim 17, Akiyama teaches a method comprising generating bitmap data at a first control unit, connecting the first control unit with a second control unit which controls a printing engine which controls a printing operation, and driving the first and second control units with a single processor. (Figure 1 shows connection of first and second control units

Art Unit: 2609

driven by a single processor, in addition, Column 1, lines 14-22, An image forming apparatus, which is constituted by a video controller for converting code data described in a printer command system such as a page description language into pixel data, and a printer engine for forming an image on the basis of the pixel data supplied from the video controller and transferring and fixing the formed image on, e.g., a recording paper sheet, is known. A video interface connecting the video controller and the printer engine will be described below.)

With regard to claim 18, Akiyama teaches a method comprising: generating print data at a computer and transmitting the print data to the first control unit, the bitmap data being generated in accordance with the transmitted print data. (Column 5, lines 35-50, A CPU 16 receives coded image information (code data) from an external apparatus 27 such as a host computer via an external interface 17 upon execution of a control program stored in a ROM 19. The received code data is input to an image processing unit 20. The image processing unit 20 stores the input code data in a RAM 21, and interprets the code data. The external apparatus 27 such as a host computer can perform various kinds of setting operations for the controller unit 26 via the external interface 17. A RAM 18 is used as registers, and the like. A ROM 22 stores font data corresponding to the values of code data. Font data corresponding to code data are read out from the ROM 22 to convert all received code data into video data consisting of dots, and the converted data are stored in a frame memory 23).

Claim Rejections - 35 USC § 103

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

5. **Claims 4, 8, and 13** are rejected under 35 U.S.C. 103(a) as being unpatentable over **Akiyama (U.S. Patent No. 5,872,635)** in view of **Kim (U.S. Patent No. 6,433,811)**

With regard to claim 4, Akiyama teaches an image forming apparatus wherein the engine control unit is an application specific integrated circuit (ASIC). . (Column 12, lines 66-67 thru column 13, line 1, Note that the present invention may be applied to either a system constituted by a plurality of devices or an apparatus consisting of a single device.) Akiyama does not teach the engine control unit comprises a memory to store state information about the engine mechanism.

Kim teaches an engine control unit that comprises a memory to store state information about the engine mechanism. (Column 5, lines 1-6, An engine controller 206 exchanges various commands with the printer engine CPU 202, transmits address information and transmits bit-map data that are image-processed and stored in the memory 204 to the printer engine CPU 202, and controls the entire operational states, operation start time and power supplying state of the printer engine 203.)

At the time when the invention was made, it would have been obvious to one of ordinary skill in the art to include a memory unit on the engine control unit.

The suggestion/motivation for doing so would have been to increase efficiency and effectiveness of the engine control unit.

Therefore, it would have been obvious to combine Kim with Akiyama to obtain the invention as specified in claim 4.

With regard to claim 8, Akiyama teaches an image forming apparatus wherein the engine control unit is an application specific integrated circuit (ASIC). (Column 12, lines 66-67 thru column 13, line 1, Note that the present invention may be applied to either a system constituted by a plurality of devices or an apparatus consisting of a single device.)

Akiyama does not teach the engine control unit comprises a memory to store state information about the engine mechanism.

Kim teaches an engine control unit that comprises a memory to store state information about the engine mechanism. (Column 5, lines 1-6, An engine controller 206 exchanges various commands with the printer engine CPU 202, transmits address information and transmits bit-map data that are image-processed and stored in the memory 204 to the printer engine CPU 202, and controls the entire operational states, operation start time and power supplying state of the printer engine 203.)

At the time when the invention was made, it would have been obvious to one of ordinary skill in the art to include a memory unit on the engine control unit.

The suggestion/motivation for doing so would have been to increase efficiency and effectiveness of the engine control unit.

Therefore, it would have been obvious to combine Kim with Akiyama to obtain the invention as specified in claim 8.

With regard to claim 13, Akiyama teaches an image forming apparatus that includes a controller to control the engine to perform the printing operation. (Figure 2B shows an engine control unit that controls engine mechanism)

Akiyama does not teach the engine control unit comprises a memory to store state information about the engine mechanism.

Kim teaches an engine control unit that comprises a memory to store state information about the engine mechanism. (Column 5, lines 1-6, An engine controller 206 exchanges various commands with the printer engine CPU 202, transmits address information and transmits bit-map data that are image-processed and stored in the memory 204 to the printer engine CPU 202, and controls the entire operational states, operation start time and power supplying state of the printer engine 203.)

At the time when the invention was made, it would have been obvious to one of ordinary skill in the art to include a memory unit on the engine control unit.

The suggestion/motivation for doing so would have been to increase efficiency and effectiveness of the engine control unit.

Therefore, it would have been obvious to combine Kim with Akiyama to obtain the invention as specified in claim 13.

Art Unit: 2609

6. Claim 15, 19, and 20 rejected under 35 USC 103(a) as being unpatentable over Akiyama (U.S. Patent No. 5,872,635) in view of Lee (U.S. Patent No. 5,737,602).

With regard to claim 15, Akiyama teaches an image forming apparatus comprising a bi-directional data bus and a control bus. (Figure 1 shows Video I/F, a bi-directional bus, in addition, Figure 2B shows each signal of the bi-directional bus, and Figure 3 lists each signal)

Akiyama does not specifically teach a horizontal synchronization (HSYNC) signal, a page synchronization signal request signal and a page synchronization (PSYNC) signal.

Lee teaches a control bus to input and output a horizontal synchronization (HSYNC) signal, a page synchronization signal request signal and a page synchronization (PSYNC) signal. (Figure 3 shows HSYNC, PSYNC, and PSYNCRQ)

At the time when the invention was made, it would have been obvious to one of ordinary skill in the art to control the engine unit and control unit with the HSYNC, PSYNC, and PSYNCRQ signals.

The suggestion/motivation for doing so would have been to simplify the control of the image-forming device because Lee teaches practical implementation for the method and apparatus of Akiyama. Any difference would be an engineering design choice.

Therefore, it would have been obvious to combine Lee with Akiyama to obtain the invention as specified in claim 15.

With regard to claim 19, Akiyama teaches a method related to generating print data. (Explained in claim 18 rejection above)

Akiyama does not specifically teach a method further comprising: sending notification to the second control unit when the generating the bitmap data is complete; driving the printing engine in response to the sending of the notification; generating a horizontal sync (HSYNC) signal at the printing engine in response to the driving of the printing engine; and transmitting the HSYNC signal from the second control unit to the first control unit.

Lee teaches sending notification to the second control unit when the generating the bitmap data is complete; driving the printing engine in response to the sending of the notification; generating a horizontal sync (HSYNC) signal at the printing engine in response to the driving of the printing engine; and transmitting the HSYNC signal from the second control unit to the first control unit. (Column 3, lines 41-60 First, when engine unit 200 is prepared to operate, engine controller 220 outputs a ready signal RDY to inform controller 120 of this condition. After the ready signal RDY is provided to controller 120, controller 120 provides a print command signal PRINT to engine controller 220. In response to the print command signal PRINT, engine controller 220 drives a motor (not shown), picks up the paper, moves the paper to a position where printing can occur, and provides a page synchronous request signal PSYNCRQ to controller 120. After the page synchronous request signal PSYNCRQ is provided to controller 120, controller 120 outputs a page synchronous signal PSYNC to engine controller 220. At this time, controller 120 transmits line data having the bit map data format corresponding to one scan line to engine controller 220 in synchronism with a horizontal synchronous signal HSYNC which is periodically generated by engine controller 220. Then, after receiving the line data, engine controller 220 enables printing of the data on paper.)

At the time when the invention was made, it would have been obvious to one of ordinary skill in the art to include the process of controlling the engine control unit and control unit from the Lee reference in the method related to generating print data taught by Akiyama, because Lee teaches practical implementation for the method and apparatus of Akiyama.

The suggestion/motivation for doing so would have been an engineering design choice.

Therefore, it would have been obvious to combine Lee with Akiyama to obtain the invention as specified in claim 19.

With regard to claim 20, Akiyama teaches a method related to generating print data.

(Explained in claim 18 and 19 rejections above)

Akiyama does not specifically teach determining that an RPM of a motor of the printing engine has reached a predetermined value; transmitting a page sync (PSYNC) request signal from the first control unit to the second control unit in response to the transmitting of the HSYNC signal and the determining of the RPM; feeding a paper for printing when the second control unit receives the PSYNC request signal; and transmitting a PSYNC signal from the second control unit to the first control unit when a sensor of the printing engine senses the fed paper. (Column 1, lines 26-29 the speed of a driving motor in an engine unit remains constant and a period of the horizontal synchronous signal HSYNC for receiving the data of the one scan line is also constant and Column 3, lines 41-60 First, when engine unit 200 is prepared to operate, engine controller 220 outputs a ready signal RDY to inform controller 120 of this condition. After the ready signal RDY is provided to controller 120, controller 120 provides a print command signal PRINT to engine controller 220. In response to the print command signal

Art Unit: 2609

PRINT, engine controller 220 drives a motor (not shown), picks up the paper, moves the paper to a position where printing can occur, and provides a page synchronous request signal PSYNCRQ to controller 120. After the page synchronous request signal PSYNCRQ is provided to controller 120, controller 120 outputs a page synchronous signal PSYNC to engine controller 220. At this time, controller 120 transmits line data having the bit map data format corresponding to one scan line to engine controller 220 in synchronism with a horizontal synchronous signal HSYNC which is periodically generated by engine controller 220. Then, after receiving the line data, engine controller 220 enables printing of the data on paper.)

At the time when the invention was made, it would have been obvious to one of ordinary skill in the art to include the process of controlling the engine control unit and control unit from the Lee reference in the method related to generating print data taught by Akiyama, because Lee teaches practical implementation for the method and apparatus of Akiyama.

The suggestion/motivation for doing so would have been an engineering design choice.

Therefore, it would have been obvious to combine Lee with Akiyama to obtain the invention as specified in claim 20.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Lawrence E. Wills whose telephone number is 571-270-3145. The examiner can normally be reached on Monday-Friday 7:30 AM - 4:00 PM EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Alexander Eisen can be reached on 571-272-7687. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2609

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

LEW
May 7, 2007



**ALEXANDER EISEN
PRIMARY EXAMINER
TECHNOLOGY CENTER 2600**